Altona Theatre Technical Specifications

as at October 2023

Further specifications, standard rig patch sheets & diagrams, patch maps, equipment manuals, inventory listings, stage floor & grid loading specifications, and other useful information is available on the Altona City Theatre Technical Services Website: http://www.altonacitytheatre.com.au/techservices/

	\mathbf{a}	ca	•	1	n
_	. LJ	La		w	

Street address	115 Civic Parade Altona, Victoria, 3018		
Loading dock	Rear of building. 3m wide x 4m high; tray height 1.1m. Direct access to stage through fire door (3m wide x 5m high).		

Auditorium

Auditorium	
Seating capacity	252 raked, no restricted viewing including 2 house seats, and 4 wheelchair seats (effective capacity 246)
Accessible seating space	Ramp entrances at ends of row D Seats C1 & C2 and C17 & C18 removed as standard to accommodate wheelchairs
Lighting	Strand Ambit GT house light system (controlled from Stage Manager's desk and Control Room) LED strip lighting of stairs and entrance ramps

Stage

Proscenium arch 9m wide x 4.75m high Setting line Front edge of proscenium arch Measurements SL to DS edge of fixed stage 0.8m SL = Setting Line SL to DS edge of Orchestra Pit 2.3m CL = Centre Line SL to first fly line 1.15m SL to ground row kickboard 6.5m SL to last upstage fly line (cyclorama) 7.15m SL to rear wall 7.3m CL to proscenium arch tormentor 4.5m CL to DS apron side wall 5.7m CL to DS apron side wall 5.7m CL to PS wall 8.4m CL to OP winches (mounted on wall) 7.9m See Stage Dimensions document for a simplified diagram Wing depth PS: 2m (wing edge of leg curtain to wall) OP: 1.5m (wing edge of leg curtain to hoist barrier) Trapdoor 2.1m from SL to front edge, 1.4m from CL to side edge Dimensions 0.54m x 0.69m Stage floor load limit 750kg/m² or 450kg point load (excluding Orchestra Pit covers) See Stage Floor & Grid Specifications document for more details	Stage		
MeasurementsSL to DS edge of fixed stage0.8mSL = Setting LineSL to DS edge of Orchestra Pit2.3mCL = Centre LineSL to first fly line1.15mSL to ground row kickboard6.5mSL to last upstage fly line (cyclorama)7.15mSL to rear wall7.3mCL to proscenium arch tormentor4.5mCL to DS apron side wall5.7mCL to PS wall8.4mCL to OP winches (mounted on wall)7.9mSee Stage Dimensions document for a simplified diagramWing depthPS: 2m (wing edge of leg curtain to wall)OP: 1.5m (wing edge of leg curtain to hoist barrier)Trapdoor2.1m from SL to front edge, 1.4m from CL to side edgeDimensions 0.54m x 0.69mStage floor load limit750kg/m² or 450kg point load (excluding Orchestra Pit covers)	Proscenium arch	9m wide x 4.75m high	
SL = Setting Line CL = Centre Line SL to DS edge of Orchestra Pit SL to first fly line SL to ground row kickboard SL to last upstage fly line (cyclorama) SL to rear wall 7.3m CL to proscenium arch tormentor CL to DS apron side wall 5.7m CL to PS wall 8.4m CL to OP winches (mounted on wall) T.9m See Stage Dimensions document for a simplified diagram Wing depth PS: 2m (wing edge of leg curtain to wall) OP: 1.5m (wing edge of leg curtain to hoist barrier) Trapdoor 2.1m from SL to front edge, 1.4m from CL to side edge Dimensions 0.54m x 0.69m Stage floor load limit 750kg/m² or 450kg point load (excluding Orchestra Pit covers)	Setting line	Front edge of proscenium arch	
OP: 1.5m (wing edge of leg curtain to hoist barrier) 2.1m from SL to front edge, 1.4m from CL to side edge Dimensions 0.54m x 0.69m Stage floor load limit 750kg/m² or 450kg point load (excluding Orchestra Pit covers)	SL = Setting Line	SL to DS edge of Orchestra Pit SL to first fly line SL to ground row kickboard SL to last upstage fly line (cyclorama) SL to rear wall CL to proscenium arch tormentor CL to DS apron side wall CL to PS wall CL to OP winches (mounted on wall)	2.3m 1.15m 6.5m 7.15m 7.3m 4.5m 5.7m 8.4m 7.9m
Dimensions 0.54m x 0.69m Stage floor load limit 750kg/m² or 450kg point load (excluding Orchestra Pit covers)	Wing depth	· · · · · · · · · · · · · · · · · · ·	
	Trapdoor		
	Stage floor load limit	· · · · · · · · · · · · · · · · · · ·	

Stage Tower & Rigging

Tower height

7.45m from stage floor (i.e. limited flying space above stage)

Chain hoist lines Fly system Type

Operated from OP at stage level

Total number of lines 13 Batten drift 6m

Batten type 50mm O/D pipe

Batten length 12.7m

Batten pick-ups 4 pickups at 3.2m intervals Batten WLL 40kg per metre, 300kg total

Bars can be swung on request

See Stage Floor & Grid Specifications document for more details

Cyclorama Dead hung on 13th line

9m wide, 7m drop

House curtain Motorised (18s travel time), affixed to proscenium arch. Pink.

Borders and legs Dead hung as per hanging plot

Scenery lines Up to 2 available to hirers depending on state of bars and intended use

Hanging plot Bars are spaced 500mm apart, first bar is 1150mm from setting line.

Line #	mm from SL	WLL	Allocation
1	1150	300kg	Spare
2	1650	300kg	Border & Legs
3	2150	300kg	LX1
4	2650	300kg	Moving light bar
5	3150	300kg	Border & Legs
6	3650	300kg	Spare (track)
7	4150	300kg	LX2
8	4650	300kg	Border
9	5150	300kg	Traveller curtain
10	5650	300kg	Par bar (backlight and moving lights)
11	6150	300kg	LX3
12	6650	300kg	Legs (or backdrop)
13	7150	300kg	Cyclorama

Staging units 11 x 2.4m x 1.2m CLS stage decks

3 x 1.2m x 1.2m CLS stage decks

300mm legs to suit

Orchestra Pit

Floor dimensions 9.1m wide x 2.8m deep

Structural beam in centre at 1.3m from front wall (footprint 25 x 25cm)

Roof height Under covers (downstage depth 1.3m): 2.5m

Under stage floor (remainder upstage depth 1.5m): 2.2m

Access Corridor from OP/Workshop. Door dimensions 1.1m x 2m.

Covers 10. Dimensions 0.9m x 1.45m each, weight ~25kg

Conductor opening Determined by removal of pit covers (up to full stage width)

Standard downstage-centre opening is 1.8m x 1.45m (2 covers)

Conductor podium 2.4m wide x 1.2m deep x 0.9m high

Music stands 16 x Manhasset Orchestral double-lipped stands

1 x Manhasset Regal double-width conductor's stand

18 x K&M 12235 LED sconce lights

2 x RATstands Apollo LED sconce lights (w/dimmers)

Power

32A 3Ø outlets 8 in Patch bay (PS gallery)

1 at OP stage floor 1 in Workshop

1 in HVAC Plant Room

1 in Foyer

20A GPOs 1 on PS wall

1 on OP wall

2 each on Bridges 1 & 3 1 in Green Room 4 in Control Room

10A GPOs 12 at stage level

12 at bridge level 8 in Auditorium 16 in Orchestra Pit 2 in Trapdoor 5 in Control Room

Various in Dressing Rooms, Green Room and Workshop

Lighting

Control Chamsys MagicQ PC Maxi Wing w/2 x touchscreens

Jands Event Plus 48/96

Dimmers 84 x 2.4kW per channel made up of:

1 x Jands FPX (12 x 2.4kW DMX)
1 x LSC RED3 (12 x 2.4kW DMX)
5 x Jands GP12 (12 x 2.4kW DMX)

1 x Jands 4PAK II 1 x Jands 4PAK-D

Switching 12 x 10A changeover power relays. Controlled from Control Room and

Stage Manager's desk. Direct switched (non DMX); Stage Manager's desk

has parallel switches for relays 10 thru 12 only.

DMX distribution 2 x Enttec ODE

1 x Enttec Storm 24 3 x 4-way DMX splitters

DMX inlets Control Room (2)

Production desk

DMX outlets Prompt side wing (Stage Manager's desk)

Opposite prompt wing FOH boom positions

Lanterns 26 x Strand Cantata 1.2kW 18/32° Profiles

8 x Strand Cantata 1.2kW 26/44° Profiles 14 x CCT Silhouette 30 1kW 22/40° Profiles 8 x Selecon SPX 800w 15/35° Profiles

8 x Selecon SPX 800w 25/50° Profiles 8 x Selecon Acclaim Axial 600w 24/44° Profiles 2 x ETC Source Four Zoom 575w 15/30° Profile

1 x ETC Source Four Jr Zoom 575w 25/50° Profile w/iris

12 x CCT Minuette 650w 17/35° Profiles 12 x Strand Patt 23 500w 20° Profiles

32 x Strand Cantata 1.2kW Fresnels w/barndoors 6 x Selecon Compact 1.2kW Fresnels w/barndoors 15 x CCT Minuette 650w Fresnels

6 x Strand Patt 123 500w Fresnels

16 x Par 64 (VNSP, 120v)

8 x Par 56 (MFL) 5 x Par 36 Pinspots

12 x Par 16 Birdies (240v)

6 x 4-way LDR Rima A500F Pro Cyc Battens (500w per cell) 5 x 4-way Quartzcolor Orion Groundrows (1kW per cell)

4 x Strand Patt 137 500w Floods

2 x 2-way Molefay Duet

Intelligent fixtures

2 x Martin ERA 600 Performance Moving Heads

8 x Chauvet Rogue R2 Spot Moving Heads

8 x Chauvet Intimidator Wash Zoom 450 Moving Heads

18 x Event Lighting PARRGBW12x8 LED Pars 20 x Chauvet SlimPAR Pro Tri LED Pars 4 x Nitec ULTRA PAR UV LED Pars 4 x ETC ColorSource Cyc Floods

1 x 2.7kW Geni Golden Strobe

Followspots

2 x Strand Solo CSI (1kW CID)
2 x Strand Solo 2K (2kW tungsten)
1 x Prolite FS12-2.0K (2kW tungsten)
1 x CCT Silhouette 15 (2kW tungsten)

Smoke/haze

2 x Antari Z-1500II DMX Smoke Machines

1 x Jem Hazer Pro DMX Hazer

Hardware

8 x 600mm² boom pipe base plates

8 x 3m boom pipes 18 x boom arms

24 x 185mm² City Theatrical 150mm top hats 6 x 125mm² City Theatrical 100mm top hats 2 x 245mm² City Theatrical 205mm top hats

5 x 190mm² ETC 6" half hats 1 x 190mm² ETC 3" short top hat

Standard rig

9 cell open whitewash

3 x 3 cells downlight specials (9 grid)

Front & top side two colour wash (warm & cold)

Back & mid side LED colour wash

Back colour beams

Top and bottom rear molefays Shinbusters / low side white

Birdie footlights

Deckles

4 colour cyclorama (battens & groundrow)

Mirror ball and pinspots*

UV LED pars*

8 x moving spot lights*

^{*} additional charges apply. See Technical Services website for patch sheet & diagram.

Audio

Mixer Behringer X32 Compact (32 XLR + 6 aux inputs / 8 DCA / 16 aux / 6

matrices)

Midas DL32 digital snake Behringer S16 digital snake

FOH speakers 2 x Meyer Sound UPJ-1P (left / right)

2 x Meyer Sound UPJunior (centre) 2 x Meyer Sound USW-1P subwoofers

5 x Meyer Sound UPM-1P (optional front fill & centre delay)

Foldback speakers 2 x RCF ART300A (above stage)

1 x Tannoy V8 (above apron)

2 x Bose 802-II (wings)

1 x Yamaha MS101-4 (Stage Manager monitor)

Powered speakers 3 x Quest QSA200i

2 x Yamaha MS20S

Standard sends FOH

Stage & Wings Foldback

Wired microphones Vocal

1 x AKG D880

1 x Audio Technica AT2020 6 x Behringer XM1800S

Instrument

2 x Shure SM57

1 x Sennheiser e906

2 x AKG D770

6 x AKG P170

3 x Rode M3

2 x Behringer C2

5 x Sennheiser MZA 900 P preamps w/ME2 lapels and

4 x Rode violin clips

2 x Countryman I2 double bass/cello mounts

1 x Bartlett Cello Mic

1 x Shure Beta 52A

3 x Sennheiser e904

3 x Shure Beta 91

Boundary

2 x Audio Technica UniPoint U853A

2 x Bartlett TM-125C (floor)

Lectern

1 x Audix ADX218 (lectern gooseneck)

Wireless microphones 32 x Sennheiser ew 112 G3 bodypack systems w/JAG IM5A headsets

5 x Sennheiser SKM 100-845 G3 handheld mics (to suit above receivers) 1 x Sennheiser SKM 100-835 G3 handheld mic (to suit above receivers)

Playback 3 x Denon DN-C615 CD Players

1 x Sony CDP-D500 CD Player

NB: Cassette tape playback not available

DIS 4 x BSS AR-133 (active)

5 x Behringer DI100 (active)

2 x Radial USB-Pro (USB stereo)

1 x ARX Blue DI (Bluetooth stereo)

System processing 1 x Behringer DCX2496 (on FOH)

Headphone distribution 16 x Behringer P16-M personal mixers w/P16-MB mounting brackets

2 x Behringer P16-D distributors 10 x AKG K99 headphones 3 x AKG K52 headphones 2 x Shure SE215-CL earphones

Microphone stands 10 x K&M 210/9 black boom stands

7 x K&M 21070 black boom stands 10 x K&M 259 black short boom stands

8 x K&M 260 black straight stands (cast iron base)

2 x Generic desk stands (cast iron base)

4 x K&M 24030 drum rim mounts

Standard rig 1 x Behringer XM1800S microphone on prompt side w/stand

Radial USB-Pro DI and minijack computer inputs in Control Room

CD playback through 2 x Denon DN-C615 (no cassette tape)

Sony CDP-D500 patched to foyer (for pre-recorded announcements)

FOH system configured for LR stereo operation with summed centre downfill. Alternative LCR configuration provides independent centre

channel coverage with front fills & centre delay.

Communications

Talkback/Cans system Sound Developments Concert Intercom (2 channel)

Substations 9

Headsets 9 x Beyerdynamic DT108

Standard rig Master station in audio rack next to audio desk

Substations on prompt desk, OP desk, lighting desk and followspots

Video

Projectors 2 x NEC NP4100 w/2 x NP09ZL lenses, 1 x NP08ZL lens

One permanently rigged on Bridge 1 w/Wahlberg DMX projector shutter

Scan converters 2 x Beneston (Video Access) VCF-009 HDMI/VGA/Composite to HD-SDI

1 x Decimator Design MD-DUCC HD-SDI to HDMI/YPbPr

Cameras 1 x Marshall CV344 w/VS-M2812A lens (colour)

1 x Marshall CV343-CS w/VS-M2812-2 lens (infrared)

2 x JVC GR-D250AA

Illumination 2 x 15 LED infrared illuminators permanently rigged on Bridge 1

2 x 4 LED infrared illuminators

Switching 1 x Blackmagic Design ATEM Television Studio HD

Distribution 1 x PRO2 SDI8SP HD-SDI splitter

1 x PRO2 SDI4SP HD-SDI splitter

1 x Kramer Electronics VM-10xl (10 x composite BNC out)

2 x 4-way composite BNC splitters 3 x 2-way composite BNC splitters 1 x Wahlberg DMX video fader **Conductor monitors**

2 x NEC NLT-15G monitors permanently rigged on Bridge 1

Standard rig

FHD colour stage cam splits to: Stage Manager's desk (PS)

Assistant Stage Manager's desk (OP)

Orchestra Pit Green Room (x 2)

HD colour stage cam splits to:

Dressing Rooms 1 & 2

Foyer

Rear foyer (stage door entrance)

Workshop

FHD infrared stage cam splits to:

Stage Manager's desk Lighting operator

CD/Laptop timecode cam splits to:

Stage Manager's desk

Assistant Stage Manager's desk

Lighting operator

Production Desk

Location Auditorium rows I and J, seats 8-11

Technical Facilities 2 x tables available, accommodating 2 people each

Dimmable desk lamps

Patch points for talkback, 2 x audio sends, DMX

Double GPO

This control location is only set up on request.

Backstage Facilities

Dressing Rooms 2, each accommodates 10-15 people

6 makeup mirrors Costume hanging rack

Green Room Accommodates 75+ people

2 x Portable costume hanging racks

5 x Full length mirrors

Concertina wall splits room in half as required

Show Relay and Paging HD CCTV monitors throughout

Audio relay speakers in Dressing Rooms, Green Room and Car Park

Paging microphone on Stage Manager's desk

Furniture 5 x 2.5m trestle tables

Approx 50 x padded chairs

Amenities 1 x Male and 1 x Female WC at stage level

2 x Male and 2 x Female WC in Green Room

1 x Male and 1 x Female shower in Green Room

Front of House Facilities

Points of Sale Ticket Box

Front of House Manager's desk (staffed by Council)

Kiosk (staffed by Council)

Show Relay and Paging CCTV monitor with audio relay on FOH Manager's desk

Internal phone to Control Room for FOH Manager & Kiosk Pre-recorded audience calls sent from Control Room Venue-wide paging available from Control Room

Amenities 2 x Male WC (including accessible / baby change table)

3 x Male urinals

5 x Female WC (including accessible / baby change table)